Technical Data Sheet Revised: 2016-05-10 | 1/1



Art.-No.: 6.1170.0355 6.1170.0655 6.1170.0955 6.1170.1255

1170

Fine Line Tape Green

Characteristics

4CR 1170 High Temperature Fine Line Tape uses a thermally stabilized PVC backing with a rubber based pressure sensitive adhesive. This tape is designed to offer a high degree of conformability without excessive stretch. 4CR 1170 will hold and cleanly remove from surfaces in temperatures up to 132°C for at least 30 minutes. 4CR 1170 assures the user of a quick laydown, no residue on demask and a sharp, clean separation line.

Tech Tip

Highly flexible tape for multi colour and design paint jobs. Easy to curve.

Application

Preferred for medium to high temperature applications where a sharp fine line is required. 4CR 1170 is used where a tape must meet a variety of paint masking applications.



Technical Data

Carrier PVC
Colour Green
Adhesive Rubber
Thickness 0.137mm

Width 3mm, 6mm, 9mm and 12mm (+/- 1mm)

Length 55m (+/- 0.1m)
Tensile strength 245 N/100mm
Elongation at break 150 % ASTM-D-1000

Heat resistance Takes a double bake at 132°C

Storage and Transportation

One year from date of receipt by customer when stored at 22°C (72°F) and 50% relative humidity.