

Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 21

SDS No.: 317263 V003.0

Revision: 17.03.2022

printing date: 24.11.2022

Replaces version from: 16.12.2021

LOCTITE SI 5980 BK TB100ML EGFD

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE SI 5980 BK TB100ML EGFD

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Silicone sealant

1.3. Details of the supplier of the safety data sheet

Henkel Ireland

Operations and Research Limited Tallaght Business Park, Whitestown

24 Dublin

Ireland

Phone: +353 (0353) 1 404 6444

HRADublin@henkel.com

For Safety Data Sheet updates please visit our website https://mysds.henkel.com/index.html#/appSelection or www.henkel-adhesives.com.

1.4. Emergency telephone number

00353 14046280

National Poisons Information Centre: Members of Public: +353 (1) 809 2166. (8.00 a.m. to 10.00 p.m. 7 days a week) Healthcare Professionals: +353 (1) 809 2566 (24-hour service)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

The substance or mixture is not hazardous according to Regulation (EC) No 1272/2008 (CLP).

2.2. Label elements

Label elements (CLP):

The substance or mixture is not hazardous according to Regulation (EC) No 1272/2008 (CLP).

Supplemental information Contains: Trimethoxyvinylsilane; 3-aminopropyltriethoxysilane May produce an allergic

reaction.

Safety data sheet available on request.

2.3. Other hazards

None if used properly.

This mixture contains components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB).

Self-classification according to Article 12(b) of (EU) 1272/2008.

Following substances are present in a concentration >= 0.1% and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

| octamethylcyclotetrasiloxane | PBT/vPvB |
|------------------------------|----------|
| 556-67-2 | |

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

| Hazardous components CAS-No. EC Number REACH-Reg No. | Concentration | Classification | Specific Conc. Limits, M- factors and ATEs | Add. Information |
|---|---------------|---|---|---------------------|
| Hexamethyldisiloxane 107-46-0 203-492-7 01-2119496108-31 | 0,25-< 2,5 % | Flam. Liq. 2, H225 Aquatic Acute 1, H400 Aquatic Chronic 2, H411 | M acute = 1 | |
| 3-aminopropyltriethoxysilane 919-30-2 213-048-4 01-2119480479-24 | 0,1-< 1 % | Skin Sens. 1B, H317 Skin Corr. 1B, H314 Acute Tox. 4, Oral, H302 | | |
| Trimethoxyvinylsilane 2768-02-7 220-449-8 01-2119513215-52 | 0,1-< 1 % | Flam. Liq. 3, H226 Acute Tox. 4, Inhalation, H332 STOT RE 2, H373 Skin Sens. 1B, H317 | | |
| Hexamethyldisilizane 999-97-3 213-668-5 01-2119438176-38 | 0,1-< 1 % | Flam. Liq. 2, H225 Acute Tox. 4, Oral, H302 Acute Tox. 3, Dermal, H311 Acute Tox. 4, Inhalation, H332 Aquatic Chronic 3, H412 | inhalation:ATE = 10,1 mg/l;vapour | |
| octamethylcyclotetrasiloxane 556-67-2 209-136-7 01-2119529238-36 | 0,01-< 0,1 % | Aquatic Chronic 1, H410 Repr. 2, H361f Flam. Liq. 3, H226 | M chronic = 10 | SVHC PBT/vPvB |

For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Prolonged or repeated contact may cause skin irritation.

Prolonged or repeated contact may cause eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

water, carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx) can be released. Silicon dioxide

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes.

Ensure adequate ventilation.

Wear protective equipment.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid skin and eye contact.

See advice in section 8

Hygiene measures:

Good industrial hygiene practices should be observed.

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction.

Refer to Technical Data Sheet

7.3. Specific end use(s) Silicone sealant

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for

Ireland

| Ingredient [Regulated substance] | ppm | mg/m ³ | Value type | Short term exposure limit category / Remarks | Regulatory list |
|---|-----|-------------------|------------------------------|--|-----------------|
| Limestone 1317-65-3 [CALCIUM CARBONATE] | | 4 | Time Weighted Average (TWA): | | IR_OEL |
| Limestone 1317-65-3 [CALCIUM CARBONATE] | | 10 | Time Weighted Average (TWA): | | IR_OEL |
| Calcium carbonate 471-34-1 [CALCIUM CARBONATE] | | 4 | Time Weighted Average (TWA): | | IR_OEL |
| Calcium carbonate 471-34-1 [CALCIUM CARBONATE] | | 10 | Time Weighted Average (TWA): | | IR_OEL |
| Calcium carbonate 471-34-1 [DUSTS NON-SPECIFIC] | | 4 | Time Weighted Average (TWA): | | IR_OEL |
| Calcium carbonate 471-34-1 [DUSTS NON-SPECIFIC] | | 10 | Time Weighted Average (TWA): | | IR_OEL |

Occupational Exposure Limits

Valid for

Great Britain

| Ingredient [Regulated substance] | gredient [Regulated substance] ppm mg/m³ Value type | | Value type | Short term exposure limit category / Remarks | Regulatory list | |
|--|---|----|------------------------------|--|-----------------|--|
| Limestone 1317-65-3 [CALCIUM CARBONATE, INHALABLE DUST] | | 10 | Time Weighted Average (TWA): | | EH40 WEL | |
| Limestone 1317-65-3 [CALCIUM CARBONATE, RESPIRABLE DUST] | | 4 | Time Weighted Average (TWA): | | EH40 WEL | |
| Limestone 1317-65-3 [LIMESTONE, RESPIRABLE MARBLE, RESPIRABLE] | | 4 | Time Weighted Average (TWA): | | EH40 WEL | |
| Limestone 1317-65-3 [LIMESTONE, TOTAL INHALABLE MARBLE, TOTAL INHALABLE] | | 10 | Time Weighted Average (TWA): | | EH40 WEL | |
| Calcium carbonate 471-34-1 [CALCIUM CARBONATE, INHALABLE DUST] | | 10 | Time Weighted Average (TWA): | | EH40 WEL | |
| Calcium carbonate 471-34-1 [CALCIUM CARBONATE, RESPIRABLE DUST] | | 4 | Time Weighted Average (TWA): | | EH40 WEL | |
| Calcium carbonate 471-34-1 [LIMESTONE, RESPIRABLE MARBLE, RESPIRABLE] | | 4 | Time Weighted Average (TWA): | | EH40 WEL | |
| Calcium carbonate 471-34-1 [LIMESTONE, TOTAL INHALABLE MARBLE, TOTAL INHALABLE] | | 10 | Time Weighted Average (TWA): | | EH40 WEL | |
| Calcium carbonate 471-34-1 [Dust, inhalable dust] | | 10 | Time Weighted Average (TWA): | | EH40 WEL | |
| Calcium carbonate | | 4 | Time Weighted Average | | EH40 WEL | |

| 471-34-1 | | (TWA): | |
|-------------------------|--|--------|--|
| [Dust, respirable dust] | | | |

Predicted No-Effect Concentration (PNEC):

| Name on list | Environmental Compartment | Exposure period | Value | | Remarks | | |
|--|------------------------------------|-----------------|-----------------|-----|----------------|--------|--|
| | Compartment | periou | mg/l | ppm | mg/kg | others | |
| Hexamethyldisiloxane | aqua | | 0,002 mg/l | | | | |
| 107-46-0 Hexamethyldisiloxane | (freshwater) aqua (marine | | 0,0002 | | | | |
| 107-46-0 | water) | | mg/l | | | | |
| Hexamethyldisiloxane | sediment | | Ü | | 0,37 mg/kg | | |
| 107-46-0 | (freshwater) | | | | | | |
| Hexamethyldisiloxane 107-46-0 | sediment (marine water) | | | | 0,037 mg/kg | | |
| Hexamethyldisiloxane | Soil | | | | 0,073 | | |
| 107-46-0 | | | | | mg/kg | | |
| Hexamethyldisiloxane 107-46-0 | Sewage treatment plant | | 10 mg/l | | | | |
| 3-Aminopropyltriethoxysilane 919-30-2 | aqua (marine water) | | 0,05 mg/l | | | | |
| 3-Aminopropyltriethoxysilane 919-30-2 | sediment (marine water) | | | | 0,18 mg/kg | | |
| 3-Aminopropyltriethoxysilane | Soil | | | | 0,069 | | |
| 919-30-2 | | | 0.04 | | mg/kg | | |
| 3-Aminopropyltriethoxysilane 919-30-2 | sewage treatment plant (STP) | | 0,81 mg/l | | | | |
| 3-Aminopropyltriethoxysilane | aqua | | 0,5 mg/l | | | | |
| 919-30-2 | (freshwater) | | | | 1.0 4 | | |
| 3-Aminopropyltriethoxysilane 919-30-2 | sediment (freshwater) | | | | 1,8 mg/kg | | |
| Trimethoxyvinylsilane | aqua | | 0,4 mg/l | | | | |
| 2768-02-7 | (freshwater) | | | | | | |
| Trimethoxyvinylsilane | aqua (marine | | 0,04 mg/l | | | | |
| 2768-02-7 Trimethoxyvinylsilane | water) Freshwater - | | 1,21 mg/l | | | | |
| 2768-02-7 | intermittent | | 1,21 mg/1 | | | | |
| Trimethoxyvinylsilane 2768-02-7 | sediment (freshwater) | | | | 1,5 mg/kg | | |
| Trimethoxyvinylsilane 2768-02-7 | sediment (marine water) | | | | 0,15 mg/kg | | |
| Trimethoxyvinylsilane 2768-02-7 | Soil | | | | 0,06 mg/kg | | |
| 1,1,1,3,3,3-Hexamethyldisilazane 999-97-3 | aqua (freshwater) | | 0,25 mg/l | | | | |
| 1,1,1,3,3,3-Hexamethyldisilazane 999-97-3 | aqua (marine water) | | 0,025 mg/l | | | | |
| 1,1,1,3,3,3-Hexamethyldisilazane | sediment | | | | 0,45 mg/kg | | |
| 999-97-3 | (freshwater) | | | | | | |
| 1,1,1,3,3,3-Hexamethyldisilazane 999-97-3 | sediment (marine water) | | | | 0,045 mg/kg | | |
| 1,1,1,3,3,3-Hexamethyldisilazane | Soil | | | | 0,22 mg/kg | | |
| 999-97-3 | | | | | | | |
| 1,1,1,3,3,3-Hexamethyldisilazane 999-97-3 | sewage treatment plant (STP) | | 67 mg/l | | | | |
| Octamethylcyclotetrasiloxane | aqua | | 0,0015 | | | | |
| 556-67-2 | (freshwater) | | mg/l | | | | |
| Octamethylcyclotetrasiloxane 556-67-2 | aqua (marine water) | | 0,00015 mg/l | | | | |
| Octamethylcyclotetrasiloxane 556-67-2 | sewage treatment plant (STP) | | 10 mg/l | | | | |
| Octamethylcyclotetrasiloxane 556-67-2 | sediment (freshwater) | | | | 3 mg/kg | | |
| Octamethylcyclotetrasiloxane | sediment | | | | 0,3 mg/kg | | |
| 556-67-2 | (marine water) | | | | | | |
| Octamethylcyclotetrasiloxane 556-67-2 | oral | | | | 41 mg/kg | | |
| Octamethylcyclotetrasiloxane 556-67-2 | Soil | | | | 0,54 mg/kg | | |

Derived No-Effect Level (DNEL):

| Name on list | Application Area | Route of Exposure | Health Effect | Exposure Time | Value | Remarks |
|--|---------------------|----------------------|--|------------------|------------|---------|
| Hexamethyldisiloxane 107-46-0 | Workers | inhalation | Acute/short term exposure - systemic effects | | 53,4 mg/m3 | |
| Hexamethyldisiloxane 107-46-0 | Workers | dermal | Acute/short term exposure - systemic effects | | 333 mg/kg | |
| Hexamethyldisiloxane 107-46-0 | Workers | inhalation | Long term exposure - systemic effects | | 53,4 mg/m3 | |
| Hexamethyldisiloxane 107-46-0 | Workers | dermal | Long term exposure - systemic effects | | 333 mg/kg | |
| Hexamethyldisiloxane 107-46-0 | General population | inhalation | Acute/short term exposure - systemic effects | | 13,3 mg/m3 | |
| Hexamethyldisiloxane 107-46-0 | General population | dermal | Acute/short term exposure - systemic effects | | 167 mg/kg | |
| Hexamethyldisiloxane 107-46-0 | General population | oral | Acute/short term exposure - systemic effects | | 0,27 mg/kg | |
| Hexamethyldisiloxane 107-46-0 | General population | inhalation | Long term exposure - systemic effects | | 13,3 mg/m3 | |
| Hexamethyldisiloxane 107-46-0 | General population | dermal | Long term exposure - systemic effects | | 167 mg/kg | |
| Hexamethyldisiloxane 107-46-0 | General population | oral | Long term exposure - systemic effects | | 0,27 mg/kg | |
| 3-Aminopropyltriethoxysilane 919-30-2 | General population | oral | Long term exposure - systemic effects | | 1 mg/kg | |
| 3-Aminopropyltriethoxysilane 919-30-2 | General population | inhalation | Long term exposure - systemic effects | | 3,5 mg/m3 | |
| 3-Aminopropyltriethoxysilane 919-30-2 | General population | dermal | Long term exposure - systemic effects | | 1 mg/kg | |
| 3-Aminopropyltriethoxysilane 919-30-2 | Workers | inhalation | Long term exposure - systemic effects | | 14 mg/m3 | |
| 3-Aminopropyltriethoxysilane 919-30-2 | Workers | dermal | Long term exposure - systemic effects | | 2 mg/kg | |
| Trimethoxyvinylsilane 2768-02-7 | Workers | dermal | Long term exposure - systemic effects | | 3,9 mg/kg | |
| Trimethoxyvinylsilane 2768-02-7 | Workers | inhalation | Long term exposure - systemic effects | | 27,6 mg/m3 | |
| Trimethoxyvinylsilane 2768-02-7 | General population | dermal | Long term exposure - systemic effects | | 7,8 mg/kg | |
| Trimethoxyvinylsilane 2768-02-7 | General population | inhalation | Long term exposure - systemic effects | | 6,7 mg/m3 | |
| Trimethoxyvinylsilane 2768-02-7 | General population | oral | Long term exposure - systemic effects | | 0,3 mg/kg | |
| 1,1,1,3,3,3-Hexamethyldisilazane 999-97-3 | Workers | inhalation | Long term exposure - systemic effects | | 53 mg/m3 | |
| 1,1,1,3,3,3-Hexamethyldisilazane 999-97-3 | Workers | inhalation | Acute/short term exposure - systemic effects | | 53 mg/m3 | |
| 1,1,1,3,3,3-Hexamethyldisilazane 999-97-3 | Workers | inhalation | Long term exposure - local effects | | 133 mg/m3 | |
| 1,1,1,3,3,3-Hexamethyldisilazane 999-97-3 | Workers | inhalation | Acute/short term exposure - local | | 133 mg/m3 | |

| | | | effects | | |
|--|--------------------|------------|--|-----------|--|
| 1,1,1,3,3,3-Hexamethyldisilazane 999-97-3 | Workers | dermal | Long term exposure - systemic effects | 7,5 mg/kg | |
| 1,1,1,3,3,3-Hexamethyldisilazane 999-97-3 | Workers | dermal | Acute/short term exposure - systemic effects | 7,5 mg/kg | |
| 1,1,1,3,3,3-Hexamethyldisilazane 999-97-3 | General population | inhalation | Long term exposure - systemic effects | 3,7 mg/m3 | |
| 1,1,1,3,3,3-Hexamethyldisilazane 999-97-3 | General population | inhalation | Acute/short term exposure - systemic effects | 3,7 mg/m3 | |
| 1,1,1,3,3,3-Hexamethyldisilazane 999-97-3 | General population | inhalation | Long term exposure - local effects | 1,7 mg/m3 | |
| 1,1,1,3,3,3-Hexamethyldisilazane 999-97-3 | General population | inhalation | Acute/short term exposure - local effects | 1,7 mg/m3 | |
| 1,1,1,3,3,3-Hexamethyldisilazane 999-97-3 | General population | oral | Long term exposure - systemic effects | 1,1 mg/kg | |
| 1,1,1,3,3,3-Hexamethyldisilazane 999-97-3 | General population | oral | Acute/short term exposure - systemic effects | 1,1 mg/kg | |
| Octamethylcyclotetrasiloxane 556-67-2 | Workers | inhalation | Long term exposure - systemic effects | 73 mg/m3 | |
| Octamethylcyclotetrasiloxane 556-67-2 | Workers | inhalation | Long term exposure - local effects | 73 mg/m3 | |
| Octamethylcyclotetrasiloxane 556-67-2 | General population | inhalation | Long term exposure - systemic effects | 13 mg/m3 | |
| Octamethylcyclotetrasiloxane 556-67-2 | General population | inhalation | Long term exposure - local effects | 13 mg/m3 | |
| Octamethylcyclotetrasiloxane 556-67-2 | General population | oral | Long term exposure - systemic effects | 3,7 mg/kg | |

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.

Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.

Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state liquid
Delivery form paste
Colour black
Odor alcohol-like

Flash point > 100,00 °C (> 212 °F) pH Not available. Density 1,3200 g/cm3 None

()

9.2. Other information

Other information not applicable for this product

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts with oxidants, acids and lyes

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Stable under normal conditions of storage and use.

Excessive heat.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

None if used for intended purpose.

SECTION 11: Toxicological information

General toxicological information:

Methanol released during polymerisation of RTV silicones is toxic by inhalation. It is also highly flammable

Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances | Value | Value | Species | Method |
|---------------------------|-------|----------------|---------|---|
| CAS-No. | type | | | |
| Hexamethyldisiloxane | LD50 | > 12.000 mg/kg | rat | not specified |
| 107-46-0 | | | | |
| 3- | LD50 | 1.457 mg/kg | rat | OECD Guideline 401 (Acute Oral Toxicity) |
| aminopropyltriethoxysilan | | | | |
| e | | | | |
| 919-30-2 | | | | |
| Trimethoxyvinylsilane | LD50 | 7.120 mg/kg | rat | OECD Guideline 401 (Acute Oral Toxicity) |
| 2768-02-7 | | | | |
| Hexamethyldisilizane | LD50 | 851 mg/kg | rat | OECD Guideline 401 (Acute Oral Toxicity) |
| 999-97-3 | | | | |
| octamethylcyclotetrasilox | LD50 | > 4.800 mg/kg | rat | equivalent or similar to OECD Guideline 401 (Acute Oral |
| ane | | | | Toxicity) |
| 556-67-2 | | | | |

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances | Value | Value | Species | Method |
|---------------------------|-------|---------------|---------|--|
| CAS-No. | type | | | |
| Hexamethyldisiloxane | LD50 | > 2.000 mg/kg | rat | equivalent or similar to OECD Guideline 402 (Acute |
| 107-46-0 | | | | Dermal Toxicity) |
| 3- | LD50 | 4.076 mg/kg | rabbit | OECD Guideline 402 (Acute Dermal Toxicity) |
| aminopropyltriethoxysilan | | | | |
| e | | | | |
| 919-30-2 | | | | |
| Trimethoxyvinylsilane | LD50 | 3.200 mg/kg | rabbit | OECD Guideline 402 (Acute Dermal Toxicity) |
| 2768-02-7 | | | | |
| Hexamethyldisilizane | LD50 | 547 mg/kg | rat | OECD Guideline 402 (Acute Dermal Toxicity) |
| 999-97-3 | | | | |
| octamethylcyclotetrasilox | LD50 | > 2.375 mg/kg | rat | equivalent or similar to OECD Guideline 402 (Acute |
| ane | | | | Dermal Toxicity) |
| 556-67-2 | | | | |

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances | Value | Value | Test atmosphere | Exposure | Species | Method |
|---------------------------|----------|-------------|-----------------|----------|---------|---------------------------|
| CAS-No. | type | | | time | | |
| Hexamethyldisiloxane | LC50 | 106 mg/l | dust/mist | 4 h | rat | OECD Guideline 403 (Acute |
| 107-46-0 | | | | | | Inhalation Toxicity) |
| 3- | LC50 | > 7,35 mg/l | dust/mist | 4 h | rat | OECD Guideline 403 (Acute |
| aminopropyltriethoxysilan | | | | | | Inhalation Toxicity) |
| e | | | | | | |
| 919-30-2 | | | | | | |
| Trimethoxyvinylsilane | LC50 | 16,8 mg/l | vapour | 4 h | rat | OECD Guideline 403 (Acute |
| 2768-02-7 | | | | | | Inhalation Toxicity) |
| Hexamethyldisilizane | Acute | 10,1 mg/l | vapour | | | Expert judgement |
| 999-97-3 | toxicity | | | | | |
| | estimate | | | | | |
| | (ATE) | | | | | |
| octamethylcyclotetrasilox | LC50 | 36 mg/l | dust/mist | 4 h | rat | OECD Guideline 403 (Acute |
| ane | | | | | | Inhalation Toxicity) |
| 556-67-2 | | | | | | |

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Exposure time | Species | Method |
|---------------------------------|----------------|------------------|---------|--|
| Hexamethyldisiloxane | not irritating | 4 h | rabbit | equivalent or similar to OECD Guideline 404 (Acute |
| 107-46-0 | | | | Dermal Irritation / Corrosion) |
| 3- | corrosive | 1 h | rabbit | OECD Guideline 404 (Acute Dermal Irritation / Corrosion) |
| aminopropyltriethoxysilan | | | | |
| e | | | | |
| 919-30-2 | | | | |
| Trimethoxyvinylsilane 2768-02-7 | not irritating | | rabbit | other guideline: |
| octamethylcyclotetrasilox | not irritating | | rabbit | equivalent or similar to OECD Guideline 404 (Acute |
| ane | | | | Dermal Irritation / Corrosion) |
| 556-67-2 | | | | |

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Exposure time | Species | Method |
|--|----------------------|---------------|---------|--|
| Hexamethyldisiloxane 107-46-0 | not irritating | | rabbit | equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion) |
| 3- aminopropyltriethoxysilan e 919-30-2 | highly irritating | | rabbit | equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion) |
| Trimethoxyvinylsilane 2768-02-7 | not irritating | | rabbit | OECD Guideline 405 (Acute Eye Irritation / Corrosion) |
| octamethylcyclotetrasilox ane 556-67-2 | not irritating | | rabbit | equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion) |

${\bf Respiratory\ or\ skin\ sensitization:}$

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Test type | Species | Method |
|--|-------------------------------|------------------------------|------------|---|
| Hexamethyldisiloxane 107-46-0 | not sensitising | | human | Patch Test |
| 3- aminopropyltriethoxysilan e 919-30-2 | Sub-Category 1B (sensitising) | Buehler test | guinea pig | OECD Guideline 406 (Skin Sensitisation) |
| Trimethoxyvinylsilane 2768-02-7 | sensitising | Buehler test | guinea pig | OECD Guideline 406 (Skin Sensitisation) |
| octamethylcyclotetrasilox ane 556-67-2 | not sensitising | Guinea pig maximisation test | guinea pig | OECD Guideline 406 (Skin Sensitisation) |

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Type of study / Route of administration | Metabolic activation / Exposure time | Species | Method |
|--|----------|--|--|---------|---|
| Hexamethyldisiloxane 107-46-0 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| Hexamethyldisiloxane 107-46-0 | negative | in vitro mammalian chromosome aberration test | with and without | | equivalent or similar to OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) |
| Hexamethyldisiloxane 107-46-0 | negative | mammalian cell gene mutation assay | with and without | | OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) |
| 3- aminopropyltriethoxysilan e 919-30-2 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| 3- aminopropyltriethoxysilan e 919-30-2 | negative | in vitro mammalian chromosome aberration test | with and without | | OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) |
| aminopropyltriethoxysilan e 919-30-2 | negative | mammalian cell gene mutation assay | with and without | | OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) |
| Trimethoxyvinylsilane 2768-02-7 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| Trimethoxyvinylsilane 2768-02-7 | positive | in vitro mammalian chromosome aberration test | with and without | | OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) |
| Trimethoxyvinylsilane 2768-02-7 | negative | mammalian cell gene mutation assay | with and without | | OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) |
| Hexamethyldisilizane 999-97-3 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| Hexamethyldisilizane 999-97-3 | negative | mammalian cell gene mutation assay | with and without | | OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) |
| octamethylcyclotetrasilox ane 556-67-2 | negative | bacterial gene mutation assay | with and without | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| octamethylcyclotetrasilox ane 556-67-2 | negative | in vitro mammalian chromosome aberration test | with and without | | equivalent or similar to OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) |
| octamethylcyclotetrasilox ane 556-67-2 | negative | mammalian cell gene mutation assay | with and without | | equivalent or similar to OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) |
| Hexamethyldisiloxane 107-46-0 | negative | intraperitoneal | | rat | equivalent or similar to OECD Guideline 475 (Mammalian Bone Marrow Chromosome Aberration Test) |
| 3- aminopropyltriethoxysilan e 919-30-2 | negative | intraperitoneal | | mouse | OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test) |
| Trimethoxyvinylsilane 2768-02-7 | negative | intraperitoneal | | mouse | other guideline: |
| octamethylcyclotetrasilox ane 556-67-2 | negative | inhalation | | rat | equivalent or similar to OECD Guideline 475 (Mammalian Bone Marrow Chromosome Aberration Test) |
| octamethylcyclotetrasilox ane 556-67-2 | negative | oral: gavage | | rat | equivalent or similar to OECD Guideline 478 (Genetic Toxicology: Rodent Dominant Lethal Test) |

Carcinogenicity

No data available.

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result / Value | Test type | Route of application | Species | Method |
|--|-------------------------------------|-----------------------------|-----------------------|---------|---|
| Hexamethyldisiloxane 107-46-0 | NOAEL P >= 5000 ppm | two- generation study | inhalation: vapour | rat | OECD Guideline 416 (Two- Generation Reproduction Toxicity Study) |
| Trimethoxyvinylsilane 2768-02-7 | NOAEL P 250 mg/kg | one- generation study | oral: gavage | rat | OECD Combined Repeated Dose and Reproductive / Developmental Toxicity Screening Test (Precursor Protocol of GL 422) |
| Trimethoxyvinylsilane 2768-02-7 | NOAEL P 1.000 mg/kg | one- generation study | oral: gavage | rat | OECD Combined Repeated Dose and Reproductive / Developmental Toxicity Screening Test (Precursor Protocol of GL 422) |
| Trimethoxyvinylsilane 2768-02-7 | NOAEL F1 1.000 mg/kg | one- generation study | oral: gavage | rat | OECD Combined Repeated Dose and Reproductive / Developmental Toxicity Screening Test (Precursor Protocol of GL 422) |
| octamethylcyclotetrasilox ane 556-67-2 | NOAEL P 300 ppm NOAEL F1 300 ppm | two- generation study | inhalation | rat | equivalent or similar to OECD Guideline 416 (Two- Generation Reproduction Toxicity Study) |

STOT-single exposure:

No data available.

STOT-repeated exposure::

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result / Value | Route of application | Exposure time / Frequency of treatment | Species | Method |
|--|--------------------|-----------------------|--|---------|---|
| Hexamethyldisiloxane 107-46-0 | NOAEL 160 mg/kg | oral: gavage | 28 d once daily (7d/w) | rat | OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents) |
| 3- aminopropyltriethoxysilan e 919-30-2 | NOAEL 200 mg/kg | oral: gavage | 90 d daily | rat | OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents) |
| Trimethoxyvinylsilane 2768-02-7 | NOAEL < 62,5 mg/kg | oral: gavage | 42d daily | rat | OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test) |
| Trimethoxyvinylsilane 2768-02-7 | NOAEL 0,605 mg/l | inhalation: vapour | 5 days/week for 14 weeks 6 hours/day | rat | not specified |
| octamethylcyclotetrasilox ane 556-67-2 | LOAEL 35 ppm | inhalation | 6 h nose only inhalation 5 days/week for 13 weeks | rat | OECD Guideline 412 (Repeated Dose Inhalation Toxicity: 28/14-Day) |
| octamethylcyclotetrasilox ane 556-67-2 | NOAEL 960 mg/kg | dermal | 3 w 5 d/w | rabbit | equivalent or similar to OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study) |

Aspiration hazard:

No data available.

11.2 Information on other hazards

not applicable

SECTION 12: Ecological information

General ecological information:

Do not empty into drains / surface water / ground water. Self-classification according to Article 12(b) of (EU) 1272/2008.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances | Value | Value | Exposure time | Species | Method |
|---------------------------------------|-------|-----------------------------|---------------|--|--|
| CAS-No. | type | | | | |
| Hexamethyldisiloxane 107-46-0 | LC50 | 0,46 mg/l | 96 h | Oncorhynchus mykiss | OECD Guideline 203 (Fish, Acute Toxicity Test) |
| Hexamethyldisiloxane 107-46-0 | NOEC | > 0,027 mg/l | 90 d | Oncorhynchus mykiss | OECD Guideline 210 (fish early lite stage toxicity test) |
| 3-aminopropyltriethoxysilane 919-30-2 | LC50 | > 934 mg/l | 96 h | Brachydanio rerio (new name: Danio rerio) | OECD Guideline 203 (Fish, Acute Toxicity Test) |
| Trimethoxyvinylsilane 2768-02-7 | LC50 | 191 mg/l | 96 h | Oncorhynchus mykiss | OECD Guideline 203 (Fish, Acute Toxicity Test) |
| Hexamethyldisilizane 999-97-3 | LC50 | 88 mg/l | 96 h | Brachydanio rerio (new name: Danio rerio) | OECD Guideline 203 (Fish, Acute Toxicity Test) |
| octamethylcyclotetrasiloxane 556-67-2 | NOEC | 0,0044 mg/l | 93 d | Salmo gairdneri (new name: Oncorhynchus mykiss) | EPA OPPTS 797.1600 (Fish Early Life Stage Toxicity Test) |
| octamethylcyclotetrasiloxane 556-67-2 | LC50 | Toxicity > Water solubility | 96 h | Oncorhynchus mykiss | EPA OTS 797.1400 (Fish Acute Toxicity Test) |

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|--|---------------|-----------------------------|---------------|---------------|---|
| 3-aminopropyltriethoxysilane 919-30-2 | EC50 | 331 mg/l | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |
| Trimethoxyvinylsilane 2768-02-7 | EC50 | 168,7 mg/l | 48 h | Daphnia magna | EU Method C.2 (Acute Toxicity for Daphnia) |
| Hexamethyldisilizane 999-97-3 | EC50 | 80 mg/l | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |
| octamethylcyclotetrasiloxane 556-67-2 | EC50 | Toxicity > Water solubility | 48 h | Daphnia magna | EPA OTS 797.1300 (Aquatic Invertebrate Acute Toxicity Test, Freshwater Daphnids) |

Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances | Value | Value | Exposure time | Species | Method |
|---------------------------------------|-------|-----------|---------------|---------------|--|
| CAS-No. | type | | | | |
| Hexamethyldisiloxane 107-46-0 | NOEC | 0,08 mg/l | 21 d | Daphnia magna | OECD 211 (Daphnia magna, Reproduction Test) |
| Trimethoxyvinylsilane 2768-02-7 | NOEC | 28,1 mg/l | 21 d | Daphnia magna | OECD 211 (Daphnia magna, Reproduction Test) |
| octamethylcyclotetrasiloxane 556-67-2 | NOEC | 7.9 μg/l | 21 d | Daphnia magna | EPA OTS 797.1330 (Daphnid Chronic Toxicity Test) |

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances | Value | Value | Exposure time | Species | Method |
|------------------------------|-------|------------------|---------------|---------------------------------|---------------------------|
| CAS-No. | type | | | | |
| Hexamethyldisiloxane | EC50 | Toxicity > Water | 70 h | Pseudokirchneriella subcapitata | |
| 107-46-0 | | solubility | | | Growth Inhibition Test) |
| Hexamethyldisiloxane | EC10 | 0,09 mg/l | 70 h | Pseudokirchneriella subcapitata | OECD Guideline 201 (Alga, |
| 107-46-0 | | | | | Growth Inhibition Test) |
| 3-aminopropyltriethoxysilane | EC50 | > 1.000 mg/l | 72 h | Scenedesmus subspicatus (new | OECD Guideline 201 (Alga, |
| 919-30-2 | | | | name: Desmodesmus subspicatus) | Growth Inhibition Test) |
| 3-aminopropyltriethoxysilane | NOEC | 1,3 mg/l | 72 h | Scenedesmus subspicatus (new | OECD Guideline 201 (Alga, |
| 919-30-2 | | | | name: Desmodesmus | Growth Inhibition Test) |
| | | | | subspicatus) | |
| Trimethoxyvinylsilane | EC50 | > 957 mg/l | 72 h | Desmodesmus subspicatus | EU Method C.3 (Algal |
| 2768-02-7 | | | | | Inhibition test) |
| Trimethoxyvinylsilane | NOEC | 957 mg/l | 72 h | Desmodesmus subspicatus | EU Method C.3 (Algal |
| 2768-02-7 | | | | | Inhibition test) |
| Hexamethyldisilizane | NOEC | 2,7 mg/l | 72 h | Scenedesmus subspicatus (new | OECD Guideline 201 (Alga, |
| 999-97-3 | | | | name: Desmodesmus | Growth Inhibition Test) |
| | | | | subspicatus) | |
| Hexamethyldisilizane | EC50 | 19 mg/l | 72 h | Scenedesmus subspicatus (new | OECD Guideline 201 (Alga, |
| 999-97-3 | | | | name: Desmodesmus | Growth Inhibition Test) |
| | EG50 | T ' ' 177 . | 0.61 | subspicatus) | ED 4 OFG 707 1050 (41 1 |
| octamethylcyclotetrasiloxane | EC50 | Toxicity > Water | 96 h | Selenastrum capricornutum | EPA OTS 797.1050 (Algal |
| 556-67-2 | | solubility | | (new name: Pseudokirchneriella | Toxicity, Tiers I and II) |
| | EC10 | 0.022/1 | 0.6 1- | subcapitata) | EDA OTC 707 1050 (A11 |
| octamethylcyclotetrasiloxane | EC10 | 0,022 mg/l | 96 h | Selenastrum capricornutum | EPA OTS 797.1050 (Algal |
| 556-67-2 | | | | (new name: Pseudokirchneriella | Toxicity, Tiers I and II) |
| | | | | subcapitata) | |

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|--|---------------|-----------------------------|---------------|---|---|
| Hexamethyldisiloxane 107-46-0 | EC50 | Toxicity > Water solubility | 3 h | activated sludge, domestic | OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test) |
| 3-aminopropyltriethoxysilane 919-30-2 | EC10 | 13 mg/l | 5 h | not specified | other guideline: |
| Trimethoxyvinylsilane 2768-02-7 | EC50 | > 100 mg/l | 3 h | activated sludge of a predominantly domestic sewage | OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test) |
| octamethylcyclotetrasiloxane 556-67-2 | EC50 | Toxicity > Water solubility | 3 h | activated sludge | ISO 8192 (Test for Inhibition of Oxygen Consumption by Activated Sludge) |

12.2. Persistence and degradability

| Hazardous substances | Result | Test type | Degradability | Exposure | Method |
|--|----------------------------|-----------|---------------|----------|---|
| CAS-No. | | | | time | |
| Hexamethyldisiloxane 107-46-0 | not readily biodegradable. | aerobic | 2 % | 28 d | OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I)) |
| 3-aminopropyltriethoxysilane 919-30-2 | not readily biodegradable. | aerobic | 67 % | 28 d | EU Method C.4-A (Determination of the "Ready" BiodegradabilityDissolved Organic Carbon (DOC) Die-Away Test) |
| Trimethoxyvinylsilane 2768-02-7 | not readily biodegradable. | aerobic | 51 % | 28 d | OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test) |
| Hexamethyldisilizane 999-97-3 | not readily biodegradable. | no data | 15,3 % | 28 d | OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test) |
| octamethylcyclotetrasiloxane 556-67-2 | not readily biodegradable. | aerobic | 3,7 % | 29 d | OECD Guideline 310 (Ready BiodegradabilityCO2 in Sealed Vessels (Headspace Test) |

12.3. Bioaccumulative potential

| Hazardous substances | Bioconcentratio | Exposure time | Temperature | Species | Method |
|------------------------------|-----------------|---------------|-------------|-----------------|--------------------------------|
| CAS-No. | n factor (BCF) | | | | |
| Hexamethyldisiloxane | 776 - 2.410 | 70 d | | Cyprinus carpio | OECD Guideline 305 C |
| 107-46-0 | | | | | (Bioaccumulation: Test for the |
| | | | | | Degree of Bioconcentration in |
| | | | | | Fish) |
| octamethylcyclotetrasiloxane | 12.400 | 28 d | | Pimephales | EPA OTS 797.1520 (Fish |
| 556-67-2 | | | | promelas | Bioconcentration Test-Rainbow |
| | | | | _ | Trout) |

12.4. Mobility in soil

| Hazardous substances CAS-No. | LogPow | Temperature | Method |
|---------------------------------------|--------|-------------|--|
| Hexamethyldisiloxane 107-46-0 | 5,06 | 20 °C | other guideline: |
| octamethylcyclotetrasiloxane 556-67-2 | 6,488 | 25,1 °C | OECD Guideline 123 (Partition Coefficient (1-Octanol / Water), Slow- Stirring Method) |

12.5. Results of PBT and vPvB assessment

| Hazardous substances CAS-No. | PBT / vPvB | |
|--|---|--|
| Hexamethyldisiloxane 107-46-0 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. | |
| 3-aminopropyltriethoxysilane 919-30-2 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. | |
| Trimethoxyvinylsilane 2768-02-7 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. | |
| Hexamethyldisilizane 999-97-3 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. | |
| octamethylcyclotetrasiloxane 556-67-2 | Fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. | |

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Do not empty into drains / surface water / ground water.

Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

 $08\ 04\ 09*$ waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information

14.1. UN number

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.2. UN proper shipping name

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.3. Transport hazard class(es)

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.4. Packing group

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.5. Environmental hazards

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.6. Special precautions for user

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

< 5 %

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009): Prior Informed Consent (PIC) (Regulation (EU) No 649/2012): Persistent organic pollutants (Regulation (EU) 2019/1021):

Not applicable Not applicable Not applicable

VOC content

(2010/75/EC)

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text ${\bf r}$

of all abbreviations indicated by codes in this safety data sheet are as follows:

H225 Highly flammable liquid and vapor.

H226 Flammable liquid and vapor.

H302 Harmful if swallowed.

H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H332 Harmful if inhaled.

H361f Suspected of damaging fertility.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

ED: Substance identified as having endocrine disrupting properties

EU OEL: Substance with a Union workplace exposure limit
EU EXPLD 1: Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2 Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC: Substance of very high concern (REACH Candidate List)
PBT: Substance fulfilling persistent, bioaccumulative and toxic criteria

PBT/vPvB: Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very

bioaccumulative criteria

vPvB: Substance fulfilling very persistent and very bioaccumulative criteria

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (ua-productsafety.de@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.