

TECHNICAL DATA SHEET



Product code: 5391 Sector: Automotive / Commercial

Issue No: 2 Issue Date: 27/06/22

UNIVERSAL BRAKE FLUID DOT 4

Brake & Clutch Fluid

Application

Suitable for passenger car, light commercial (LCV) and heavy goods vehicles (HGV). Designed for high performance braking systems where a non-mineral fluid is required and high braking temperatures are experienced.

Equilibrium Reflux Boiling Point above 260°C

Wet Equilibrium Boiling Point above 165°C

Performance Profile

U.S. FMVSS No.116 DOT 4

SAE J 1704, SAE J 1703

Typical Characteristics

Kinematic Viscosity @100 °C, cSt 2.41

Density @ 20 1.05

Features & Benefits

- Enhanced performance against water absorption, which improves resistance to vapour lock.
- Compatible with DOT 3 brake fluid.

Technical & Health and Safety

T: 01484 475060

E: technical@millersoils.co.uk

For H&S info or SDS, please visit our website

www.millersoils.co.uk

Footnotes: Always refer to manufacturer handbook prior to use.



MADE IN BRITAIN

Millers Oils Ltd
Brighouse West Yorkshire HD6 3DP UK
Tel: +44(0) 1484 713201
www.millersoils.co.uk