

ENGINE FLUSH

Page: 1

Compilation date: 13/05/2010

Revision date: 23/10/2019

Revision No: 1c

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: ENGINE FLUSH

Product code: 5777

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: Millers Oils Ltd

Hillside Oilworks
Rastrick Common

Brighouse

West Yorkshire

HD6 3DP

United Kingdom

Tel: +44 (0)1484 713201 **Fax:** +44 (0)1484 721263

Email: h.s@millersoils.co.uk

1.4. Emergency telephone number

Emergency tel: +44 (0)1484 713201

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Asp. Tox. 1: H304; Eye Irrit. 2: H319; -: EUH208

Most important adverse effects: Contains benzenesulfonic acid, mono-c16-24-alkyl derivs, calcium salts. May produce

an allergic reaction. May be fatal if swallowed and enters airways. Causes serious eye

irritation.

2.2. Label elements

Label elements:

Hazard statements: EUH208: Contains benzenesulfonic acid, mono-c16-24-alkyl derivs, calcium salts. May

produce an allergic reaction.

H304: May be fatal if swallowed and enters airways.

H319: Causes serious eye irritation.

ENGINE FLUSH

Page: 2

Hazard pictograms: GHS07: Exclamation mark

GHS08: Health hazard





Signal words: Danger

Precautionary statements: P264: Wash hands thoroughly after handling.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P301+310: IF SWALLOWED: Immediately call a.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P331: Do NOT induce vomiting.

P337+313: If eye irritation persists: Get medical attention.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

HYDROCARBONS, C15-C20,N-ALKANES, ISOALKANES, CYCLICS, <0.03% AROMATICS - REACH registered number(s): 01-2119487077-29-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent
934-956-3	-	-	Asp. Tox. 1: H304	70-90%

PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR)ESTERS, ZINC SALT - REACH registered number(s): 01-2119493626-26-XXXX

283-392-8	-	-	Skin Irrit. 2: H315; Eye Dam. 1: H318;	1-10%
			Aquatic Chronic 2: H411	

BENZENESULFONIC ACID, MONO-C16-24-ALKYL DERIVS, CALCIUM SALTS - REACH registered number(s): 01-2119492616-28-XXXX

274-263-7 70024-69-0 - Skin Sens. 1B: H317 <1%	
--	--

O,O,O-TRIPHENYL PHOSPHOROTHIOATE - REACH registered number(s): 01-2119979545-21-XXXX

209-909-9	-	-	Repr. 2: H361fd	<1%
-----------	---	---	-----------------	-----

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water. Remove all contaminated clothes and

footwear immediately unless stuck to skin.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Do not induce vomiting. Consult a doctor.

ENGINE FLUSH

Page: 3

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach

pain may occur.

Inhalation: No symptoms.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers. Carbon dioxide. Alcohol resistant foam. Dry chemical powder.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Turn leaking containers leak-

side up to prevent the escape of liquid. Mark out the contaminated area with signs and

prevent access to unauthorised personnel.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Avoid the formation or spread of mists in the air.

ENGINE FLUSH

Page: 4

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. The floor of the

storage room must be impermeable to prevent the escape of liquids.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: No data available.

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves.Eye protection: Safety glasses.Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Pale brown

Odour: Barely perceptible odour

Evaporation rate: Negligible

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Insoluble

Also soluble in: Most organic solvents.

Viscosity: Non-viscous

Kinematic viscosity: 8.1 cSt

Viscosity test method: Kinematic viscosity in 10-6 m2/s at 40°C (ISO 3104/3105)

Boiling point/range°C: No data available. **Melting point/range°C:** No data available.

Flammability limits %: lower: No data available. upper: No data available.

Flash point°C: 140 Part.coeff. n-octanol/water: No data available.

Autoflammability°C: No data available. **Vapour pressure:** No data available.

Relative density: 0.85 **pH:** No data available.

VOC g/l: No data available.

ENGINE FLUSH

Page: 5

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

HYDROCARBONS, C15-C20,N-ALKANES, ISOALKANES, CYCLICS, <0.03% AROMATICS

DERMAL	RBT	LD50	>3160	mg/kg
DUST/MIST	RAT	LD50	>5266	mg/kg
ORAL	RAT	LD50	5000	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Serious eye damage/irritation	OPT	Hazardous: calculated
Aspiration hazard	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach

pain may occur.

Inhalation: No symptoms.

ENGINE FLUSH

Page: 6

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

HYDROCARBONS, C15-C20,N-ALKANES, ISOALKANES, CYCLICS, <0.03% AROMATICS

DAPHNIA	48H EC50	>3193	mg/l
FISH	96H LC50	>1028	mg/l
MARINE ALGAE (Skeletonema costatum)	72H ErC50	>10000	mg/l

PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR)ESTERS, ZINC SALT

ALGAE	72H ErC50	600	mg/l
Daphnia magna	48H EC50	23	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50	4.5	mg/l

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

Disposal of packaging: Arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

ENGINE FLUSH

Page: 7

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

2015/830.

Conforms to regulation (EC) No 1907/2006 (REACH)

Phrases used in s.2 and s.3: EUH208: Contains <name of sensitising substance>. May produce an allergic reaction.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H318: Causes serious eye damage.H319: Causes serious eye irritation.

H361fd: Suspected of damaging fertility. Suspected of damaging the unborn child.

H411: Toxic to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.