



SAFETY DATA SHEET

CVL EXTRA

Page: 1

Compilation date: 30/11/2007

Revision date: 13/12/2021

Revision No: 1d

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: CVL EXTRA

Product code: 5792

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: High octane booster

1.3. Details of the supplier of the safety data sheet

Company name: Millers Oils Ltd
Hillside Oilworks
Rastrick Common
Brighouse
West Yorkshire
HD6 3DP
United Kingdom

Tel: +44 (0)1484 713201

Fax: +44 (0)1484 721263

Email: h.s@millersoils.co.uk

1.4. Emergency telephone number

Emergency tel: +44 (0)1484 713201

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Eye Dam. 1: H318; Asp. Tox. 1: H304; Carc. 2: H351; Repr. 1B: H360FD; STOT SE 3: H336; Aquatic Chronic 1: H410; -: EUH066

Most important adverse effects: Repeated exposure may cause skin dryness or cracking. May be fatal if swallowed and enters airways. Causes serious eye damage. May cause drowsiness or dizziness. Suspected of causing cancer. May damage fertility. May damage the unborn child. Very toxic to aquatic life with long lasting effects.

2.2. Label elements

Label elements:

Hazard statements: EUH066: Repeated exposure may cause skin dryness or cracking.

[cont...]

SAFETY DATA SHEET

CVL EXTRA

Page: 2

H304: May be fatal if swallowed and enters airways.

H318: Causes serious eye damage.

H336: May cause drowsiness or dizziness.

H351: Suspected of causing cancer.

H360FD: May damage fertility. May damage the unborn child.

H410: Very toxic to aquatic life with long lasting effects.

Hazard pictograms: GHS05: Corrosion

GHS07: Exclamation mark

GHS08: Health hazard

GHS09: Environmental



Signal words: Danger

Precautionary statements: P261: Avoid breathing vapours.

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P301+310: IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331: Do NOT induce vomiting.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405: Store locked up.

P501: Dispose of contents/container to disposal should be in accordance with local, state or national legislation.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

HYDROCARBONS, C10, AROMATICS, <1% NAPHTHALENE - REACH registered number(s): 01-2119463583-34-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent
918-811-1	-	-	Asp. Tox. 1: H304; STOT SE 3: H336; Aquatic Chronic 2: H411; -: EUH066	50-70%

[cont...]

SAFETY DATA SHEET

CVL EXTRA

Page: 3

HYDROCARBONS, C10, AROMATICS, >1% NAPHTHALENE - REACH registered number(s): 01-2119463588-24

919-284-0	-	-	Asp. Tox. 1: H304; Carc. 2: H351; STOT SE 3: H336; Aquatic Chronic 2: H411; -: EUH066	10-30%
-----------	---	---	---	--------

HYDROCARBONS, C10-C13, AROMATICS, >1% NAPHTHALENE - REACH registered number(s): 2119451151-53-XXXX

926-273-4	1174522-16 -7	-	Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Carc. 2: H351	1-10%
-----------	------------------	---	--	-------

POTASSIUM 1,2-BIS(2-ETHYLHEXYLOXYCARBONYL)-ETHANESULPHONATE - REACH registered number(s): 01-2119919740-39

231-308-5	7491-09-0	-	Skin Irrit. 2: H315; Eye Dam. 1: H318	1-10%
-----------	-----------	---	---------------------------------------	-------

FERROCENE - REACH registered number(s): 01-2119978280-34-XXXX

203-039-3	102-54-5	-	Flam. Sol. 1: H228; Acute Tox. 4: H302+332; Repr. 1B: H360FD; STOT RE 2: H373; Aquatic Chronic 1: H410	<1%
-----------	----------	---	--	-----

NAPHTHALENE

202-049-5	91-20-3	-	Carc. 2: H351; Acute Tox. 4: H302; Aquatic Chronic 1: H410; Aquatic Acute 1: H400	<1%
-----------	---------	---	---	-----

HYDROCARBONS, C11-14, N-ALKANES, ISOALKANES, CYCLIC, <2% AROMATICS - REACH registered number(s): 01-2119456620-43-XXXX

926-141-6	-	Substance with a Community workplace exposure limit.	Asp. Tox. 1: H304	<1%
-----------	---	---	-------------------	-----

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water. Remove all contaminated clothes and footwear immediately unless stuck to skin.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Do not induce vomiting. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be pain and redness. The eyes may water profusely. There may be severe pain.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. May cause drowsiness.

Inhalation: There may be coughing and a sore throat.

[cont...]

SAFETY DATA SHEET

CVL EXTRA

Page: 4

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises. Show this safety data sheet to the doctor in attendance.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers. Carbon dioxide. Alcohol resistant foam. Dry chemical powder.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Evacuate the area immediately. Eliminate all sources of ignition. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Keep away from sources of ignition. Keep away from direct sunlight. Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

[cont...]

SAFETY DATA SHEET

CVL EXTRA

Page: 5

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

HYDROCARBONS, C11-14, N-ALKANES, ISOALKANES, CYCLIC, <2% AROMATICS

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1200 mg/m ³	-	-	-

DNEL/PNEC Values

Hazardous ingredients:

HYDROCARBONS, C10, AROMATICS, <1% NAPHTHALENE

Type	Exposure	Value	Population	Effect
DNEL	Dermal	12.5 mg/kg bw/day	Workers	Systemic
DNEL	Inhalation	151 mg/m ³	Workers	Systemic
DNEL	Dermal (developmental tox)	7.5 mg/kg bw/day	Consumers	Systemic
DNEL	Inhalation (developmental tox)	32 mg/m ³	Consumers	Systemic
DNEL	Oral (developmental tox)	7.5 mg/kg bw/day	Consumers	Systemic

HYDROCARBONS, C10, AROMATICS, >1% NAPHTHALENE

Type	Exposure	Value	Population	Effect
DNEL	Dermal	12.5 mg/kg bw/day	Workers	Systemic
DNEL	Inhalation	151 mg/m ³	Workers	Systemic
DNEL	Dermal	7.5 mg/kg bw/day	Consumers	Systemic
DNEL	Inhalation	32 mg/m ³	Consumers	Systemic
DNEL	Oral	7.5 mg/kg bw/day	Consumers	Systemic
DNEL	Dermal	12.5 mg/kg bw/day	Workers	Systemic
DNEL	Inhalation	151 mg/m ³	Workers	Systemic
DNEL	Dermal	7.5 mg/kg bw/day	Consumers	Systemic
DNEL	Inhalation	32 mg/m ³	Consumers	Systemic
DNEL	Oral	7.5 mg/kg bw/day	Consumers	Systemic

HYDROCARBONS, C10-C13, AROMATICS, >1% NAPHTHALENE

Type	Exposure	Value	Population	Effect
DNEL	Dermal	12.5 mg/kg/day	Workers	Systemic

[cont...]

SAFETY DATA SHEET

CVL EXTRA

Page: 6

DNEL	Inhalation	151 mg/m ³	Workers	Systemic
DNEL	Dermal	7.5 mg/kg/day	Consumers	Systemic
DNEL	Inhalation	32 mg/m ³	Consumers	Systemic
DNEL	Oral	7.5 mg/kg	Consumers	Systemic

POTASSIUM 1,2-BIS(2-ETHYLHEXYLOXYCARBONYL)-ETHANESULPHONATE

Type	Exposure	Value	Population	Effect
DNEL	Dermal	13.4 mg/kg bw/day	-	-
DNEL	Inhalation	46.6 mg/m ³	-	-

FERROCENE

Type	Exposure	Value	Population	Effect
DNEL	Inhalation (repeated dose)	0.02 mg/m ³	Workers	Systemic
DNEL	Inhalation	0.04 mg/m ³	Workers	Systemic
DNEL	Dermal (repeated dose)	0.025 mg/kg bw/day	Workers	Systemic
DNEL	Inhalation (repeated dose)	0.005 mg/m ³	Consumers	Systemic
DNEL	Oral (repeated dose)	0.013 mg/kg bw/day	Consumers	Systemic

NAPHTHALENE

Type	Exposure	Value	Population	Effect
DNEL	Dermal (developmental tox)	3.57 mg/kg bw/day	Workers	Systemic
DNEL	Inhalation (developmental tox)	25 mg/m ³	Workers	Systemic
DNEL	Inhalation (developmental tox)	25 mg/m ³	Workers	Local

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Impermeable gloves.

Eye protection: Tightly fitting safety goggles. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Amber

Odour: Pungent

Evaporation rate: No data available.

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Insoluble

Viscosity: Non-viscous

Kinematic viscosity: 1.26mm²/s@

Boiling point/range°C: 160 - 220

Melting point/range°C: No data available.

Flammability limits %: lower: No data available.

[cont...]

SAFETY DATA SHEET

CVL EXTRA

Page: 7

Flash point°C: 66
Autoflammability°C: No data available.
Relative density: 0.897
VOC g/l: No data available.

upper: No data available.
Part.coeff. n-octanol/water: No data available.
Vapour pressure: No data available.
pH: No data available.

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

10.4. Conditions to avoid

Conditions to avoid: Heat. Sources of ignition. Direct sunlight.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

HYDROCARBONS, C10, AROMATICS, <1% NAPHTHALENE

DERMAL	RBT	LD50	2000	mg/kg
VAPOURS	RAT	4H LC50	>590	mg/m3

HYDROCARBONS, C10, AROMATICS, >1% NAPHTHALENE

DERMAL	RBT	LD50	2000	mg/kg
VAPOURS	RAT	4H LC50	>590	mg/m3

[cont...]

SAFETY DATA SHEET

CVL EXTRA

Page: 8

HYDROCARBONS, C10-C13, AROMATICS, >1% NAPHTHALENE

DERMAL	RBT	LD50	>2000	mg/kg
ORAL	RAT	LD50	6318.0	mg/kg
VAPOURS	RAT	4H LC50	4788	mg/m3

NAPHTHALENE

ORL	MUS	LD50	316	mg/kg
ORL	RAT	LD50	490	mg/kg
SKN	RAT	LD50	>2500	mg/kg

HYDROCARBONS, C11-14, N-ALKANES, ISOALKANES, CYCLIC, <2% AROMATICS

ORL	RAT	LD50	>5000	mg/kg
SKN	RBT	LD50	>5000	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Serious eye damage/irritation	OPT	Hazardous: calculated
Carcinogenicity	--	Hazardous: calculated
Reproductive toxicity	--	Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated
Aspiration hazard	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be pain and redness. The eyes may water profusely. There may be severe pain.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. May cause drowsiness.

Inhalation: There may be coughing and a sore throat.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

HYDROCARBONS, C10, AROMATICS, <1% NAPHTHALENE

ALGAE	72H ErC50	1-3	mg/l
DAPHNIA	48H EC50	3-10	mg/l
FISH	96H LC50	2-5	mg/l

[cont...]

SAFETY DATA SHEET

CVL EXTRA

Page: 9

HYDROCARBONS, C10, AROMATICS, >1% NAPHTHALENE

ALGAE	72H ErC50	1-3	mg/l
DAPHNIA	48H EC50	3-10	mg/l
FISH	96H LC50	2-5	mg/l

HYDROCARBONS, C10-C13, AROMATICS, >1% NAPHTHALENE

Daphnia magna	48H EC50	1.1	mg/l
Pseudokirchneriella subcapitata	72H ErC50	3.8	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50	3	mg/l

HYDROCARBONS, C11-14, N-ALKANES, ISOALKANES, CYCLIC, <2% AROMATICS

Scenedesmus Subspicatus	72H IC50	>1000	mg/l
Daphnia magna	48H EC50	>1000	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50	>1000	mg/l

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Disposal of packaging: Arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN3082

[cont...]

SAFETY DATA SHEET

CVL EXTRA

Page: 10

14.2. UN proper shipping name

Shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(Contains: hydrocarbons, C10 aromatics and ferrocene.)

14.3. Transport hazard class(es)

Transport class: 9

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: Yes

14.6. Special precautions for user

Special precautions: No special precautions.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking.

H228: Flammable solid.

H302: Harmful if swallowed.

H302+332: Harmful if swallowed or if inhaled.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H318: Causes serious eye damage.

H336: May cause drowsiness or dizziness.

H351: Suspected of causing cancer <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H360FD: May damage fertility. May damage the unborn child.

H373: May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

[cont...]

SAFETY DATA SHEET

CVL EXTRA

Page: 11

H410: Very toxic to aquatic life with long lasting effects.

H411: Toxic to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

