

Product code: 7779 Sector: Automotive

Issue No: 3 Issue Date: 09/03/21

XF PREMIUM ENGINE OIL C5 ECO 5w20

Fully synthetic, mid SAPS, for use in petrol, diesel and hybrid engines.

Application

A premium manufacturer acknowledged engine oil formulated using the latest technology for OEM applications requiring a C5 5w20 viscosity, introduced for Ford Eco-Boost petrol engines and Jaguar Land Rover.

Performance Profile

ACEA C5
API SN RC, SN
Ford WSS-M2C948-B (Acknowledged)
Ford WSS-M2C948-A (Acknowledged)
ILSAC GF-5
Jaguar Land Rover STJLR.03.5004
(Acknowledged)

Suitable for

ACEA A1/B1
Chrysler MS-6395
Fiat 9.55535-CR1
Ford WSS-M2C945-A, Ford WSS-M2C925-B
Ford WSS-M2C925-A
ILSAC GF-4
Asian manufacturers

Typical Characteristics

Density @ 15°C, g/ml	0.847
Kinematic Viscosity @ 100°C, cSt.	7.9
Flashpoint, °C	>200

Features & Benefits

- XF Premium engine oil with Millers Oils Dynamic Fluid Technology (DFT) provides enhanced low temperature flow when cold starting, instantly protecting the vital components of the engine from the very start of every journey.
- XF Premium engine oil with DFT maximises viscosity stability at high temperatures. This reduces engine wear giving superior protection for components including pistons, rings, timing chain, bearings and valve lifters.
- DFT specifically engineered to enhance engine cleanliness, delivering improved fuel economy, reduced emissions and extended service drain capability.
- DFT complements and utilises latest mid SAPS technology protecting after treatment systems such as particulate filters, Selective Catalytic Reduction (SCR) and AdBlue delivering our ultimate soot control and environmental protection.
- DFT delivers outstanding instant protection under hot and cold temperatures, whilst simultaneously reducing fuel consumption and lowering exhaust emissions.
- XF Premium engine oil with DFT is specifically formulated for use in all hybrid systems including self-charging hybrid electric vehicles (HEV) and plug in hybrid electric vehicles (PHEV).

Technical & Health and Safety

T: 01484 475060

E: technical@millersoils.co.uk

For H&S info or SDS, please visit our website

www.millersoils.co.uk

Footnotes: SAPS – Sulphated Ash, Phosphorus & Sulphur, DFT – Dynamic Fluid Technology, OEM - Original Equipment Manufacturer.
Asian manufacturers – Including but not limited to Honda, Hyundai, Infiniti, Kia, Lexus, Nissan, Suzuki and Toyota.



MADE IN BRITAIN 

Millers Oils Ltd
Brighouse West Yorkshire HD6 3DP UK
Tel: +44(0) 1484 713201
www.millersoils.co.uk