

XF PREMIUM ENGINE OIL C2 0W30 ECO

Page: 1 Compilation date: 26/01/2018 Revision date: 18/11/2020 Revision No: 1b

## Section 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

Product name: XF PREMIUM ENGINE OIL C2 0W30 ECO

Product code: 8045

1.2. Relevant identified uses of the substance or mixture and uses advised against

# 1.3. Details of the supplier of the safety data sheet

Company name:	Millers Oils Ltd	
	Hillside Oilworks	
	Rastrick Common	
	Brighouse	
	West Yorkshire	
	HD6 3DP	
	United Kingdom	
Tel:	+44 (0)1484 713201	
Fax:	+44 (0)1484 721263	
Email:	h.s@millersoils.co.uk	

**1.4. Emergency telephone number** 

Emergency tel: +44 (0)1484 713201

# Section 2: Hazards identification

## 2.1. Classification of the substance or mixture

Classification under CLP: This product has no classification under CLP.

2.2. Label elements

Label elements: This product has no label elements.

2.3. Other hazards

**PBT:** This product is not identified as a PBT/vPvB substance.

### Section 3: Composition/information on ingredients

3.2. Mixtures

# XF PREMIUM ENGINE OIL C2 0W30 ECO

#### Hazardous ingredients:

# DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC - REACH registered number(s): 01-2119484627-25-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent
265-157-1	64742-54-7	-	Asp. Tox. 1: H304	50-70%
C14-16-18 ALKYL PHENOL - REACH registered number(s): 01-2119498288-19-XXXX				

-	-	-	Skin Sens. 1B: H317; STOT RE 2:	<1%
			H373	

## Section 4: First aid measures

#### 4.1. Description of first aid measures

**Skin contact:** Wash immediately with plenty of soap and water. Remove all contaminated clothes and footwear immediately unless stuck to skin.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water. Do not induce vomiting.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so.

### 4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

## Section 5: Fire-fighting measures

#### 5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers. Carbon dioxide. Alcohol resistant foam. Dry chemical powder.

#### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

### Section 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Turn leaking containers leak-

side up to prevent the escape of liquid.

# XF PREMIUM ENGINE OIL C2 0W30 ECO

### 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

## Section 7: Handling and storage

#### 7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

7.3. Specific end use(s)

Specific end use(s): No data available.

### Section 8: Exposure controls/personal protection

### 8.1. Control parameters

Workplace exposure limits: No data available.

#### **DNEL/PNEC** Values

### Hazardous ingredients:

### DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC

Туре	Exposure	Value	Population	Effect
DNEL	Inhalation	5.4 mg/m3	Workers	Local
DNEL	Inhalation	1.2 mg/m3	Consumers	Local

### 8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Respiratory protection not required.

Hand protection: Nitrile gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

## Section 9: Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

### State: Liquid

Evaporation rate: Negligible

# XF PREMIUM ENGINE OIL C2 0W30 ECO

			<b>Page:</b> 4
Oxidising:	Non-oxidising (by EC criteria)		
Solubility in water:	Insoluble		
Kinematic viscosity:	50 cSt @40		
Boiling point/range°C:	No data available.	Melting point/range°C:	No data available.
Flammability limits %: lower:	No data available.	upper:	No data available.
Flash point°C:	>200	Part.coeff. n-octanol/water:	No data available.
Autoflammability°C:	No data available.	Vapour pressure:	No data available.
Relative density:	0.845	pH:	No data available.
VOC g/l:	No data available.		

9.2. Other information

Other information: No data available.

# Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

#### 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

## 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

#### 10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

## 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

### 11.1. Information on toxicological effects

Toxicity values: No data available.

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

**Ingestion:** There may be irritation of the throat.

Inhalation: No symptoms.

# XF PREMIUM ENGINE OIL C2 0W30 ECO

**Page:** 5

#### Section 12: Ecological information

### 12.1. Toxicity

Ecotoxicity values: No data available.

## 12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: No data available.

### 12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: No data available.

### Section 13: Disposal considerations

#### 13.1. Waste treatment methods

 Disposal operations:
 Transfer to a suitable container and arrange for collection by specialised disposal company.

 Disposal of packaging:
 Arrange for collection by specialised disposal company.

 NB:
 The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

### Section 14: Transport information

Transport class: This product does not require a classification for transport.

## Section 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

# 15.2. Chemical Safety Assessment

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

# Section 16: Other information

### Other information

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

Phrases used in s.2 and s.3: H304: May be fatal if swallowed and enters airways.

# XF PREMIUM ENGINE OIL C2 0W30 ECO

H317: May cause an allergic skin reaction.

H373: May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.