

# WOLF UNIVERSAL 2T

28/09/2023  
1900

Oil for air-cooled 2-stroke gasoline engines. Suitable for machines where the reservoir is filled with a mixture of gasoline and oil, and for those with separate reservoirs. This oil is easily miscible with gasoline and ensures a good protection of the pistons and segments from overheating.

## APPLICATIONS

This oil is applicable for all air cooled 2-stroke gasoline engines with a dilution content of 2% (1 to 50) and 4% (1 to 25). This according to the constructor's requirements.

## FEATURES

Engine protection: excellent engine performance  
Corrosion protection: adequate corrosion protection

## PERFORMANCE

API TC

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.880
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	55.3
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	8.3
Viscosity index	ASTM D2270		121
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	1.1
Pour point	ASTM D6892	°C	-15
Flash Point COC	ASTM D92	°C	106
Colour	VISUAL		RED

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium  
Tel. +32 (0)3 870 00 00

[www.wolf lubes.com](http://www.wolf lubes.com)

