

SAFETY DATA SHEET according to Regulation 1907/2006

Product name: **ProXL Generation20 High Solids 2K Clearcoat**
Creation date: 2.6.2020 · Version: 1

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name

ProXL Generation20 High Solids 2K Clearcoat

Product code

CCG20HS-5

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Coating.

Uses advised against

No information.

1.3. Details of the supplier of the safety data sheet

Manufacturer

Capella Solutions Group
1 Mantle Close
Sittingbourne, Kent, ME10 3BW
+44 (0)1634 823900

1.4. Emergency telephone number

Emergency

112

Supplier

+44(0)1634 823900

SECTION 2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Flam. Liq. 3; H226 Flammable liquid and vapour.

Asp. Tox. 1; H304 May be fatal if swallowed and enters airways.

Skin Irrit. 2; H315 Causes skin irritation.

Skin Sens. 1; H317 May cause an allergic skin reaction.

Eye Irrit. 2; H319 Causes serious eye irritation.

STOT SE 3; H335 May cause respiratory irritation.

STOT SE 3; H336 May cause drowsiness or dizziness.

STOT RE 2; H373 May cause damage to organs through prolonged or repeated exposure.

Aquatic Chronic 2; H411 Toxic to aquatic life with long lasting effects.

SAFETY DATA SHEET according to Regulation 1907/2006

Product name: **ProXL Generation20 High Solids 2K Clearcoat**
Creation date: 2.6.2020 · Version: 1

2.2 Label elements

2.2.1. Labelling according to Regulation (EC) No 1272/2008 [CLP]



Signal word: **Danger**

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe mist/vapours.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301 + P310 + P331 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. Do NOT induce vomiting.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with national regulation.

2.2.2. Contains:

xylene (CAS: 1330-20-7, EC: 215-535-7, Index: 601-022-00-9)

solvent naphtha (petroleum), light arom. (CAS: 64742-95-6, EC: 265-199-0, Index: 649-356-00-4)

n-butyl acetate (CAS: 123-86-4, EC: 204-658-1, Index: 607-025-00-1)

reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (CAS: 1065336-91-5, EC: 915-687-0)

2.2.3. Special provisions

Special hazards are not known or expected.

2.3. Other hazards

No information.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

For mixtures see 3.2.

SAFETY DATA SHEET according to Regulation 1907/2006

Product name: ProXL Generation20 High Solids 2K Clearcoat

Creation date: 2.6.2020 · Version: 1

3.2. Mixtures

Name	CAS EC Index	%	Classification according to Regulation (EC) No 1272/2008 (CLP)	Specific Conc. Limits	REACH Registration No.
xylene ^[C]	1330-20-7 215-535-7 601-022-00-9	10-25	Flam. Liq. 3; H226 Asp. Tox. 1; H304 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Acute Tox. 4; H332 STOT SE 3; H335 STOT RE 2; H373		-
solvent naphtha (petroleum), light arom. ^[P]	64742-95-6 265-199-0 649-356-00-4	10-25	Flam. Liq. 3; H226 Asp. Tox. 1; H304 STOT SE 3; H335 STOT SE 3; H336 Aquatic Chronic 2; H411 EUH066		01-2119455851-35
n-butyl acetate	123-86-4 204-658-1 607-025-00-1	10-25	Flam. Liq. 3; H226 STOT SE 3; H336 EUH066		-
reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	1065336-91-5 915-687-0 -	<0,5	Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410		-
EO bis(benzotriazolyl)phenylpropionat	104810-47-1 - -	<0,5	Skin Sens. 1; H317 Aquatic Chronic 2; H411		-

Notes for substances:

C	Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.
P	The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (Einecs No 200-753-7). When the substance is not classified as a carcinogen at least the precautionary statements (P102-)P260- P262-P301 + P310- P331 shall apply. This note applies only to certain complex oil-derived substances in Part 3.

SECTION 4. FIRST AID MEASURES

4.1. Description of first aid measures

General notes

In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Never give anything by mouth to an unconscious person. Place patient in recovery position and ensure airway patency.

Following inhalation

Remove patient to fresh air - move out of dangerous area. If symptoms develop and persist, seek medical attention. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Obtain professional medical help! In case of unconsciousness bring patient into stable side position and seek medical attention.



SAFETY DATA SHEET according to Regulation 1907/2006

Product name: **ProXL Generation20 High Solids 2K Clearcoat**
Creation date: 2.6.2020 · Version: 1

Following skin contact

Take off all contaminated clothing. Wash affected skin areas thoroughly with plenty of water and soap. If symptoms develop and persist, seek medical attention.

Following eye contact

Immediately flush eyes with running water, keeping eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation persists, seek professional medical attention.

Following ingestion

Do not induce vomiting! Vomiting may cause aspiration in the lungs. If vomiting occurs, the patient should hold the head lower than the hips, because it reduces the possibility of aspiration. Rinse mouth thoroughly with water. Immediately consult a doctor. Show the physician the safety data sheet or label.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation

Vapours may cause drowsiness and dizziness.

Symptoms include: headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, unconsciousness.

Can cause irritation of respiratory system.

Coughing, sneezing, nasal discharge, labored breathing.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidneys, liver and CNS.

Skin contact

Itching, redness, pain.

May cause sensitisation by skin contact (symptoms: itching, redness, rashes).

Repeated or prolonged contact with the product may lead to removal of natural fats from the skin and non-allergic contact dermatitis.

Eye contact

Redness, tearing, pain.

Ingestion

Aspiration into the lungs causes coughing, shortness of breath and may lead to chemical pneumonia.

May cause nausea/vomiting and diarrhea.

May cause abdominal discomfort.

4.3. Indication of any immediate medical attention and special treatment needed

-

SECTION 5. FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Carbon dioxide. Dry chemical powder. Water spray. Alcohol resistant foam.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products

In case of a fire toxic gases can be generated; do not inhale gases/smoke.

5.3. Advice for firefighters

Protective actions

In case of fire evacuate the area. In case of fire or heating do not breathe fumes/vapours. Cool containers at risk with water spray. If possible remove containers from endangered area.

SAFETY DATA SHEET according to Regulation 1907/2006

Product name: **ProXL Generation20 High Solids 2K Clearcoat**
 Creation date: 2.6.2020 · Version: 1

Special protective equipment for firefighters

Firefighters should wear appropriate protective clothing for firefighters (including helmets, protective boots and gloves) (EN 469) and self-contained breathing apparatus (SCBA) with a full face-piece (EN 137).

Additional information

Contaminated firefighting water must be disposed of in accordance with the regulations; do not allow to reach the sewage system.

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment

Use personal protective equipment (Section 8).

Emergency procedures

Ensure adequate ventilation. Keep away from sources of ignition and/or heat; No smoking! Evacuate personnel. Prevent access to unprotected personnel. Do not breathe vapour or mist. Avoid contact with skin and eyes. Do not use open fire and keep away all sources of ignition.

6.1.2. For emergency responders

Use personal protective equipment.

6.2. Environmental precautions

Do not allow product to reach water/drains/sewage systems or permeable soil. If accidental large entry into water or ground occurs, inform responsible authorities.

6.3. Methods and material for containment and cleaning up

6.3.1. For containment

Stem the spill if this does not pose risks.

6.3.2. For cleaning up

Absorb product (with inert material), collect it in special container and dispose it to a licensed hazardous-waste disposal contractor. Use spark-proof tools. Make sure the leakage site is well aired. Wear appropriate personal protective equipment. Dispose in accordance with applicable regulations (see Section 13).

6.3.3. Other information

-

6.4. Reference to other sections

See also Sections 8 and 13.

SECTION 7. HANDLING AND STORAGE

7.1. Precautions for safe handling

7.1.1. Protective measures

Measures to prevent fire

Ensure adequate ventilation. Keep away from sources of ignition - no smoking. Use spark-proof tools. Take precautionary measures against static discharges. Protect from open fire and other sources of ignition or heat. Ensure proper grounding of the equipment. Vapours and air form explosive mixtures.

Measures to prevent aerosol and dust generation

Use general or local exhaust ventilation to prevent inhaling vapours and aerosols.

Measures to protect the environment

Do not discharge into drains, surface water and soil. After use immediately close container tightly.

SAFETY DATA SHEET according to Regulation 1907/2006

Product name: **ProXL Generation20 High Solids 2K Clearcoat**

Creation date: 2.6.2020 · Version: 1

7.1.2. Advice on general occupational hygiene

Use good personal hygiene practices – wash hands at breaks and when done working with material. Do not eat, drink or smoke while working. Avoid contact with skin, eyes and clothes. Do not breathe vapours/mist. Wear suitable protective equipment; see Section 8. Refer to instructions on label and regulations for safety and health at work. Product is not for eating – do not ingest!

7.2. Conditions for safe storage, including any incompatibilities

7.2.1. Technical measures and storage conditions

Store in accordance with local regulations. Keep in tightly closed container. Store in a dry, cool and well-ventilated area, away from incompatible materials. Protect from open fire, heat and direct sunlight. Keep away from food, drink and animal feeding stuffs. Keep away from oxidising substances.

7.2.2. Packaging materials

The original container of producer.

7.2.3. Requirements for storage rooms and vessels

Close opened containers after use. Put the containers upright to prevent from leaking. Do not store in unlabelled containers.

7.2.4. Storage class

-

7.2.5. Further information on storage conditions

-

7.3. Specific end use(s)

Recommendations

-

Industrial sector specific solutions

-

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

8.1.1. Occupational exposure limit values

Name (CAS)	Limit values		Short-term exposure limit		Remarks	Biological Tolerance Values
	ml/m ³ (ppm)	mg/m ³	ml/m ³ (ppm)	mg/m ³		
Butyl acetate (123-86-4)	150	724	200	966		
Xylene, o-,m-,p- or mixed isomers (1330-20-7)	50	220	100	441	Sk, BMGV	650 mmol methyl hippuric acid/mol creatinine in urine - Post shift

8.1.2. Information on monitoring procedures

BS EN 14042:2003 Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents. BS EN 482:2012+A1:2015 Workplace exposure. General requirements for the performance of procedures for the measurement of chemical agents. BS EN 689:2018 Workplace exposure. Measurement of exposure by inhalation to chemical agents. Strategy for testing compliance with occupational exposure limit values.

8.1.3. DNEL/DMEL values

No information.

8.1.4. PNEC values

No information.

SAFETY DATA SHEET according to Regulation 1907/2006

Product name: **ProXL Generation20 High Solids 2K Clearcoat**
 Creation date: 2.6.2020 · Version: 1

8.2. Exposure controls

8.2.1. Appropriate engineering control

Substance/mixture related measures to prevent exposure during identified uses

Handle in accordance with good industrial hygiene and safety practice. Use good personal hygiene practices – wash hands at breaks and when done working with material. Do not eat, drink or smoke while working. Avoid contact with eyes and skin. Do not breathe vapours/aerosols. When choosing personal protective equipment, ask your chemical substance supplier for advice.

Organisational measures to prevent exposure

Remove all contaminated clothes immediately and wash them before reuse. Keep eyewash bottles or personal eyewash units and emergency showers available.

Technical measures to prevent exposure

Provide good ventilation and local exhaust in areas with increased concentration.

8.2.2. Personal protective equipment

Eye and face protection

Safety glasses with side protection (EN 166).

Hand protection

Protective gloves (EN 374). Observe the manufacturer's instructions regarding the use, storage, maintenance and replacement of gloves. In case of damage or at the first signs of wear and tear, change the gloves immediately. The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Skin protection

Choose body protection according to the activity and possible exposure. Cotton protective clothing and shoes that cover the entire foot (EN ISO 20345). Protective antistatic clothing EN 1149 (1:2006, 2:1998 and 3:2004, 5:2008), protective antistatic shoes (EN 20345:2012).

Respiratory protection

If the concentration limit values are exceeded, it is necessary to wear appropriate respiratory protection. Wear suitable protective breathing mask (EN 136) with filter A2-P2 (EN 14387). For dust/gas/ vapor concentrations above the applicable filter limit, in case of oxygen concentrations below 17% or in vague conditions, autonomous self-contained breathing apparatus should be used, according to standard EN 137, EN 138.

Thermal hazards

-

8.2.3. Environmental exposure controls

Instruction measures to prevent exposure

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

Technical measures to prevent exposure

Do not allow product to reach drains, sewage systems or ground water.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

-	Physical state:	liquid
-	Colour:	according to specification
-	Odour:	characteristic

SAFETY DATA SHEET according to Regulation 1907/2006

Product name: ProXL Generation20 High Solids 2K Clearcoat
 Creation date: 2.6.2020 · Version: 1

Important health, safety and environmental information

-	pH	No information.
-	Melting point/freezing point	No information.
-	Initial boiling point/boiling range	No information.
-	Flash point	No information.
-	Evaporation rate	No information.
-	Flammability (solid, gas)	No information.
-	Explosion limits (vol%)	No information.
-	Vapour pressure	No information.
-	Vapour density	No information.
-	Density	No information.
-	Solubility	No information.
-	Partition coefficient	No information.
-	Auto-ignition temperature	No information.
-	Decomposition temperature	No information.
-	Viscosity	No information.
-	Explosive properties	No information.
-	Oxidising properties	No information.

9.2. Other information

-	Remarks:	
---	-----------------	--

SECTION 10. STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

Product is stable under normal conditions of use, recommended handling and storage conditions.

10.3. Possibility of hazardous reactions

Vapours and air can form flammable or explosive mixtures.

10.4. Conditions to avoid

Protect from heat, direct sunlight, open fire, sparks.

10.5. Incompatible materials

Oxidants.

10.6. Hazardous decomposition products

Under normal use conditions no hazardous decomposition products are expected. In case of fire/explosion vapours/gases that pose a health hazard are released.

SAFETY DATA SHEET according to Regulation 1907/2006

Product name: **ProXL Generation20 High Solids 2K Clearcoat**
 Creation date: 2.6.2020 · Version: 1

SECTION 11. TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

(a) Acute toxicity

Name	Exposure route	Type	Species	Time	Value	Method	Remark
solvent naphtha (petroleum), light arom. (64742-95-6)	oral	LD ₅₀	rat		2000 – 5000 mg/kg		
solvent naphtha (petroleum), light arom. (64742-95-6)	dermal	LD ₅₀	rabbit		> 2000 mg/kg		

(b) Skin corrosion/irritation

Additional information: Causes skin irritation.

(c) Serious eye damage/irritation

Additional information: Causes serious eye irritation.

(d) Respiratory or skin sensitisation

Additional information: May cause an allergic skin reaction.

(e) (Germ cell) mutagenicity

No information.

(f) Carcinogenicity

No information.

(g) Reproductive toxicity

No information.

Summary of evaluation of the CMR properties

No information.

(h) STOT-single exposure

Additional information: May cause drowsiness or dizziness. May cause respiratory irritation.

(i) STOT-repeated exposure

Additional information: May cause damage to organs through prolonged or repeated exposure.

(j) Aspiration hazard

Additional information: May be fatal if swallowed and enters airways.

SAFETY DATA SHEET according to Regulation 1907/2006

Product name: **ProXL Generation20 High Solids 2K Clearcoat**
 Creation date: 2.6.2020 · Version: 1

SECTION 12. ECOLOGICAL INFORMATION

12.1. Toxicity

12.1.1. Acute (short-term) toxicity

For components

Substance (CAS Nr.)	Type	Value	Exposure time	Species	Organism	Method	Remark
solvent naphtha (petroleum), light arom. (64742-95-6)	LC ₅₀ /EC ₅₀ /IC ₅₀	1 – 10 mg/L		fish			
	LC ₅₀ /EC ₅₀ /IC ₅₀	1 – 10 mg/L		water crustaceans			
	LC ₅₀ /EC ₅₀ /IC ₅₀	1 – 10 mg/L		algae			
	LC ₅₀ /EC ₅₀ /IC ₅₀	> 100 mg/L		microorganisms			

12.1.2. Chronic (long-term) toxicity

No information.

12.2. Persistence and degradability

12.2.1. Abiotic degradation, physical- and photo-chemical elimination

No information.

12.2.2. Biodegradation

No information.

12.3. Bioaccumulative potential

12.3.1. Partition coefficient

No information.

12.3.2. Bioconcentration factor (BCF)

No information.

12.4. Mobility in soil

12.4.1. Known or predicted distribution to environmental compartments

No information.

12.4.2. Surface tension

No information.

12.4.3. Adsorption/Desorption

No information.

12.5. Results of PBT and vPvB assessment

No evaluation.

12.6. Other adverse effects

No information.

12.7. Additional information

For product

Toxic to aquatic life with long lasting effects.

Do not allow to reach ground water, water courses or sewage system.

SAFETY DATA SHEET according to Regulation 1907/2006

Product name: **ProXL Generation20 High Solids 2K Clearcoat**
 Creation date: 2.6.2020 · Version: 1

SECTION 13. DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

13.1.1. Product / Packaging disposal

Waste chemical

Dispose of in accordance with applicable waste disposal regulation. Disposal must be made according to official regulations: deliver it to authorised collector/remover/transformer of hazardous waste. Do not allow product to reach drains/sewage systems.

Packaging

Dispose of in accordance with applicable waste disposal regulation. Deliver completely emptied containers to approved waste disposal authorities. Empty containers represent a fire hazard as they may contain flammable product residues and vapour.

13.1.2. Waste treatment-relevant information

-

13.1.3. Sewage disposal-relevant information

-

13.1.4. Other disposal recommendations

-

SECTION 14. TRANSPORT INFORMATION

14.1. UN number

UN 1263

14.2. UN proper shipping name

PAINT

IMDG name: PAINT (solvent naphtha (petroleum), light arom. , reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate)

14.3. Transport hazard class(es)

3

14.4. Packing group

III

14.5. Environmental hazards

Additional labeling: ENVIRONMENTALLY HAZARDOUS

IMDG: MARINE POLLUTANT

14.6. Special precautions for user

Limited quantities

5 L

Tunnel restriction code

(D/E)

IMDG EmS

F-E, S-E

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Goods may not be carried in bulk in bulk containers, containers or vehicles.



SAFETY DATA SHEET according to Regulation 1907/2006

Product name: **ProXL Generation20 High Solids 2K Clearcoat**
 Creation date: 2.6.2020 · Version: 1

SECTION 15. REGULATORY INFORMATION

15.1. Safety, health and environmental regulations /legislation specific for the substance or mixture

- Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (including last amendment Commission Regulation (EU) 2015/830)
- Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

15.1.1. Information according 2004/42/EC about limitation of emissions of volatile organic compounds (VOC-guideline)

Not applicable.

15.2. Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16. OTHER INFORMATION

Indication of changes

-

Abbreviations and acronyms

ATE - Acute Toxicity Estimate
 ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road
 ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
 CEN - European Committee for Standardisation
 C&L - Classification and Labelling
 CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
 CAS# - Chemical Abstracts Service number
 CMR - Carcinogen, Mutagen, or Reproductive Toxicant
 CSA - Chemical Safety Assessment
 CSR - Chemical Safety Report
 DMEL - Derived Minimal Effect Level
 DNEL - Derived No Effect Level
 DPD - Dangerous Preparations Directive 1999/45/EC
 DSD - Dangerous Substances Directive 67/548/EEC
 DU - Downstream User
 EC - European Community
 ECHA - European Chemicals Agency
 EC-Number - EINECS and ELINCS Number (see also EINECS and ELINCS)
 EEA - European Economic Area (EU + Iceland, Liechtenstein and Norway)
 EEC - European Economic Community
 EINECS - European Inventory of Existing Commercial Substances
 ELINCS - European List of notified Chemical Substances
 EN - European Standard
 EQS - Environmental Quality Standard
 EU - European Union
 Euphrac - European Phrase Catalogue
 EWC - European Waste Catalogue (replaced by LoW – see below)
 GES - Generic Exposure Scenario
 GHS - Globally Harmonized System
 IATA - International Air Transport Association
 ICAO-TI - Technical Instructions for the Safe Transport of Dangerous Goods by Air
 IMDG - International Maritime Dangerous Goods
 IMSBC - International Maritime Solid Bulk Cargoes
 IT - Information Technology
 IUCLID - International Uniform Chemical Information Database
 IUPAC - International Union for Pure Applied Chemistry
 JRC - Joint Research Centre
 Kow - octanol-water partition coefficient

SAFETY DATA SHEET according to Regulation 1907/2006

Product name: **ProXL Generation20 High Solids 2K Clearcoat**

Creation date: 2.6.2020 · Version: 1

LC₅₀ - Lethal Concentration to 50 % of a test population
 LD₅₀ - Lethal Dose to 50% of a test population (Median Lethal Dose)
 LE - Legal Entity
 LoW - List of Wastes (see <http://ec.europa.eu/environment/waste/framework/list.htm>)
 LR - Lead Registrant
 M/I - Manufacturer / Importer
 MS - Member States
 MSDS - Material Safety Data Sheet
 OC - Operational Conditions
 OECD - Organization for Economic Co-operation and Development
 OEL - Occupational Exposure Limit
 OJ - Official Journal
 OR - Only Representative
 OSHA - European Agency for Safety and Health at work
 PBT - Persistent, Bioaccumulative and Toxic substance
 PEC - Predicted Effect Concentration
 PNEC(s) - Predicted No Effect Concentration(s)
 PPE - Personal Protection Equipment
 (Q)SAR - Qualitative Structure Activity Relationship
 REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
 RID - Regulations concerning the International Carriage of Dangerous Goods by Rail
 RIP - REACH Implementation Project
 RMM - Risk Management Measure
 SCBA - Self-Contained Breathing Apparatus
 SDS - Safety data sheet
 SIEF - Substance Information Exchange Forum
 SME - Small and Medium sized Enterprises
 STOT - Specific Target Organ Toxicity
 (STOT) RE - Repeated Exposure
 (STOT) SE - Single Exposure
 SVHC - Substances of Very High Concern
 UN - United Nations
 vPvB - Very Persistent and Very Bioaccumulative

Key literature references and sources for data

-

List of relevant H phrases

H226 Flammable liquid and vapour.
 H304 May be fatal if swallowed and enters airways.
 H312 Harmful in contact with skin.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H332 Harmful if inhaled.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.
 H373 May cause damage to organs through prolonged or repeated exposure .
 H400 Very toxic to aquatic life.
 H410 Very toxic to aquatic life with long lasting effects.
 H411 Toxic to aquatic life with long lasting effects.
 EUH066 Repeated exposure may cause skin dryness or cracking.

The information of this SDS is based on the present state of our knowledge and meets the requirements of EU and national laws. The user's working conditions however, are beyond our knowledge and control. The product is not to be used for purposes other than those specified under Section 1 without a written permission. It remains the responsibility of the user to ensure that the necessary steps are taken to meet the laws and regulations. Handling of the product may only be done by people above 18 years of age, who are satisfactorily informed of how to do the work, the hazardous properties and necessary safety precautions. The information given in this SDS is to describe the product only in terms of health and safety requirements and should not, therefore, be construed as guaranteeing specific properties.



SAFETY DATA SHEET according to Regulation 1907/2006

Product name: **ProXL Generation20 High Solids 2K Clearcoat**

Creation date: **2.6.2020** · Version: **1**
