



Technical fluids - Powersteering

Eurol Powersteering fluid C

Fully synthetic hydraulic oil for levelling and power steering systems

Description

Eurol Powersteering Fluid C is a full synthetic hydraulic fluid, especially developed for hydraulic systems like levelling systems and power steering systems in tractors, passenger cars and commercial vehicles.

Eurol Powersteering Fluid C has a very high viscosity index and a very low pour point. Due to these features, the viscosity will hardly change under varying temperatures.

Eurol Powersteering Fluid C protects the system against oxidation. Because of the high boiling point and the water resistance, the product can be applied for a long lasting and safe use when this type of fluid is prescribed.

Performance level

- Porsche 000 043 206 56
- DIN 51524/3 (HVLP)
- VW G 002 000/G 004 000
- ISO 7308
- Hyundai 00232-19017
- GM/Opel B 040 2012

Recommended for use

- Ford WSS-M2C204-A/A1
- GM/Opel 19 40 715/766
- Porsche
000.043.203.33/000.043.206.56
- Volvo 1161529/30741424
- ZF TE-ML 02K
- DTFR 31B120 (MB 345.0)
- MAN M 3289

Physical properties

Colour	Green	
Density at 20°C	0.817 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	19 cSt	ASTM D 445
Viscosity, kinematic at 100°C	6 cSt	ASTM D 445
Viscosity Index	303	ASTM D 2270
Flash point	173 °C	ASTM D 93
Pour point	-57 °C	ASTM D 97

Article number E113675
Version 2.1, 18-10-2023

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.