



Coolants & screenwash - Cooling fluids

Eurol Coolant XL -36°C

Long-life coolant, based on organic corrosion inhibitors

Description

Eurol Coolant XL -36°C is a long-life coolant, based on mono-ethylene-glycol and organic corrosion inhibitor technology (OAT technology). Since Eurol Coolant XL -36°C meets the performance level of a broad set of specifications, it can be applied a wide variety of vehicles.

This coolant is to be used undiluted, so never top-up with water. Life-time of the product is 5 years or 650.000 km for trucks or 250.000 km for passenger cars, depending on which situation occurs first.

Eurol Coolant XL -36°C is a modern coolant for water-cooled combustion engines and protects the system from freezing up to -36 °C.

This coolant is nitrite-, amine-, borate-, phosphate-, nitrate- and silicate-free and in this way, it contributes to a cleaner environment.

Eurol Coolant XL -36°C prevents from scale formation and offers an excellent protection against cavitation. Moreover, it protects metal parts in the cooling system against corrosion. This coolant is completely safe for rubber, plastics, metals or its alloys in cooling systems.

Always follow the instructions of the manufacturer regarding application of the right coolant.

Performance level

- VW TL-774 F (G12+)
- VW TL-774 D (G12)
- BS 6580
- ASTM D3306
- ASTM D4985
- ASTM D4656
- AFNOR NFR 15-601
- MB 326.3
- MAN 324 Typ SNF
- SAE J1034
- Renault Type D
- MTU MTL 5048
- Liebherr MD1-36-130
- Komatsu 07.892
- John Deere JDM H5
- JASO M325
- GM 6277M
- Ford WSS-M97B44-D
- DAF 74002
- Case New Holland MAT3624
- STJLR 651.5003

Recommended for use

- Volvo VCS

Physical properties

Colour	Yellow	
Density at 20°C	1.069 kg/l	ASTM D 4052
Flash point	111 °C	ASTM D 93
Frost protection	-36 °C	ASTM D 1177
pH	8.4	

Article number E504140
Version 2.0, 09-09-2020

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.