

TOROTEC 5W-30 LONGLIFE

Product Code: PCM013 | **Revision:** 20220907



Fully synthetic & mid SAPS automotive engine oil for VW Group.

Available Pack Sizes



Applications

A fully synthetic and mid SAPS engine oil formulated for use with petrol and diesel engines, particularly for VW Group vehicles. Our specialist Adaptive Molecular Technology maintains engine power, maintains efficiency and improves reliability whilst supporting exhaust after-treatment devices throughout the vehicle's lifecycle in all driving conditions.

Recommended by Aztec Oils as suitable for the following applications

ACEA C3
API SN/CF
BMW LL-04
Mercedes-Benz 229.51
Porsche C30
VW 504.00/507.00

Benefits

- Ensures lubricant performance over extended drain intervals.
- Excellent start-up protection.
- Exceptional long-term anti-wear and oxidation stability.
- Improved fuel efficiency.
- Maintains very high standards of engine cleanliness.
- Superior performance under both high temperature and low temperature conditions.

Typical Test Data

Density @ 15°C (kg/m ³)	ASTM D4052	0.850
Flash Point (°C)	ASTM D92	200
Kinematic Viscosity @ 40°C (mm ² /s)	ASTM D445	74
Kinematic Viscosity @ 100°C (mm ² /s)	ASTM D445	12.1
Pour Point (°C)	ASTM D97	-45
Total Base Number (mg KOH/g)	ASTM D2896	8
Viscosity Index	ASTM D2207	161

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

Health, Safety & Recommendations

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This lubricant, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is given in good faith, but without warranty.

Health, Safety & Recommendations

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Before using this product, the vehicles maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturers' recommendations.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This lubricant, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is given in good faith, but without warranty.