

PAINT REMOVER

Page: 1

Compilation date: 23/08/2016

Revision date: 10/11/2015

Revision No: 2

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Sent to: Public Server Addition.

Product name: PAINT REMOVER

Synonyms: PAINTSTRIPPER-

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Paint Releasing agent, professional users only.

1.3. Details of the supplier of the safety data sheet

Company name: Leading Solvents

Marston Business Park

Rudgate
Tockwith
York
YO26 7QF

Tel: 01423 358058 **Fax:** 01423 358923

Email: enquiries@leading-solvents.co.uk

1.4. Emergency telephone number

Emergency tel: 01423 358058 (Office Hours Only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Acute Tox. 4: H302; Carc. 2: H351; STOT SE 2: H371

Most important adverse effects: Harmful if swallowed. Suspected of causing cancer. May cause damage to organs .

2.2. Label elements

Label elements:

Hazard statements: H302: Harmful if swallowed.

H351: Suspected of causing cancer. H371: May cause damage to organs .

Signal words: Warning

Hazard pictograms: GHS07: Exclamation mark

GHS08: Health hazard





PAINT REMOVER

Page: 2

Precautionary statements: P301+310: IF SWALLOWED: Immediately call a POISON CENTER/doctor/.

P281: Use personal protective equipment as required.

P260: Do not breathe vapours.

P202: Do not handle until all safety precautions have been read and understood.

P264: Wash hands thoroughly after handling.

P270: Do not eat, drink or smoke when using this product.

P309+311: IF exposed or if you feel unwell: Call a POISON CENTRE or doctor.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

DICHLOROMETHANE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
200-838-9	75-09-2	-	Carc. 2: H351	>90%

METHANOL - REACH registered number(s): 01-2119433307-44

200-659-6	67-56-1	-	Flam. Liq. 2: H225; Acute Tox. 3: H331;	1-10%
			Acute Tox. 3: H311; Acute Tox. 3: H301;	
			STOT SE 1: H370	

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Drench the skin with plenty of water. Remove contaminated clothing and wash before

reuse. If large areas of the skin are affected or if irritation persists, seek medical advice.

Eye contact: Immediately flood the eye with plenty of water for at least 15 minutes, holding the eye

open. Remove any contact lenses and open eyes wide apart. Get medical attention if

any discomfort continues

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water

to drink immediately. Transfer to hospital as soon as possible.

Inhalation: Remove from exposure, rest and keep warm. In severe cases, or if recovery is not rapid

or complete, seek medical advice. If unconscious and breathing is OK, place in the

recovery position.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach

pain may occur. There may be vomiting.

PAINT REMOVER

Page: 3

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from

downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn

leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

PAINT REMOVER

Page: 4

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

DICHLOROMETHANE

Workplace exposure limits:

Respirable dust

UK 350 mg/m3 1060 mg/m3	State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
	UK	350 mg/m3	1060 mg/m3	-	-

METHANOL

	UK	266 mg/m3	333 mg/m3	-	-
--	----	-----------	-----------	---	---

DNEL/PNEC Values

Hazardous ingredients:

METHANOL

Type	Exposure	Value	Population	Effect
DNEL	Dermal	40 mg/kg/day	Workers	Systemic
DNEL	Inhalation	260 mg/m3	Workers	Systemic
DNEL	Dermal	40 mg/kg/day	Workers	Local
DNEL	Inhalation	260 mg/m3	Workers	Local
DNEL	Dermal	8 mg/kg/day	Consumers	Systemic
DNEL	Inhalation	50 mg/m3	Consumers	Systemic
DNEL	Oral	8 mg/kg/day	Consumers	Local

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Impermeable gloves, change regularly to avoid permeation problems. Ensure gloves

are manufactured/tested in accordance with BS EN 374.

Eye protection: Safety glasses. Safety goggles. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid
Colour: Colourless
Odour: Aromatic

PAINT REMOVER

Page: 5

Evaporation rate: Slow

Oxidising: No data available.

Solubility in water: Slightly soluble

Also soluble in: Most organic solvents.

Viscosity: No data available.

Boiling point/range°C: >35 Melting point/range°C: No data available.

Flammability limits %: lower: No data available. upper: No data available.

Flash point°C: 60 - 93 Part.coeff. n-octanol/water: No data available.

Autoflammability°C: No data available. **Vapour pressure:** No data available.

Relative density: 1.290 **pH:** No data available.

VOC g/I: No data available.

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of hydrogen chloride / phosgene.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

DICHLOROMETHANE

0.51			4==0	/*
UKI	MUS	111150	1770	ma/ka
OIL	IVIUS	LDSU	4110	mg/kg

PAINT REMOVER

Page: 6

ORL	RAT	LD50	5350	mg/kg
SCU	MUS	LD50	6460	mg/kg

METHANOL

IVN	RAT	LD50	2131	mg/kg
ORL	MUS	LD50	7300	mg/kg
ORL	RAT	LD50	5628	mg/kg

Relevant hazards for substance:

Hazard	Route	Basis
Acute toxicity (ac. tox. 4)	ING	Hazardous: calculated
Carcinogenicity		Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach

pain may occur. There may be vomiting.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

PAINT REMOVER

Page: 7

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN2810

14.2. UN proper shipping name

Shipping name: TOXIC LIQUID, ORGANIC, N.O.S.

(DICHLOROMETHANE; METHANOL)

14.3. Transport hazard class(es)

Transport class: 6.1

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E
Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H225: Highly flammable liquid and vapour.

H301: Toxic if swallowed.
H302: Harmful if swallowed.
H311: Toxic in contact with skin.

H331: Toxic if inhaled.

PAINT REMOVER

Page: 8

H351: Suspected of causing cancer <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H370: Causes damage to organs <or state all organs affected, if known> <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>. H371: May cause damage to organs <or state all organs affected, if known> <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.